

# Flash Series/Silver Odyssey Spec Sheet

Modified on: Mon, Apr 29, 2024 at 11:48 AM

# Flash Series/Silver Odyssey Spec Sheet

## DreamScape Flash/Odyssey Specification Sheet v:042224

### Product Name: Black, Gold, Silver Flash/Silver Odyssey – 20 oz. (457g/m<sup>2</sup>) Type II

- Description:** Commercial grade printable vinyl wallcovering media in black, gold and silver with highly reflective surface.
- Construction:** Polyester/vinyl face with non-woven backing
- Packaging:** 3" core, wound print side out, wrapped in black poly-bag, shipped in heavy-duty cardboard tube
- Installation:** Standard commercial wallcovering pastes, primers and techniques.

For indoor use in environmentally controlled spaces.

**SPECIAL INSTALLATION INSTRUCTION** This wallcovering contains metallic particles and can conduct electricity. To avoid possible fire hazards or electric shock, wallcovering should not come in contact with or extend into electrical-outlet boxes or light-switch boxes. Turn off all electricity to the room prior to starting installation.

**SPECIAL NOTE** Please be aware this wallcovering may interfere with broadcast signals, such as Wi-Fi and radio reception, because of the polyester/metal layer. Tests have shown 5% or less impact on signals when the receptor is totally encased in wallcovering but the interference may vary depending on the specific installation conditions.

**Ink Compatibility:** UV curable printers only

**CAUTION:** This product is highly reflective. Check with your printer manufacturer for their recommendations on printing reflective material.

**Availability:**

Roll Sizes:		US	Metric
	Widths:	54"	1.37m
	Lengths:	25yds, 50yds, 100yds	30m, 50m, 100m
	Trial Rolls:	27"x15'	.686m x 4.57m

**Weight & Thickness:**

Product Weight & Thickness:		US	Metric
Product Weight:		20oz. per lineal yard (13 oz. per sq yd)	457g/m <sup>2</sup>
Thickness		0.017in. to 0.022in.	0.432mm to 0.559mm

**Type II Properties:**

Passes all criteria for WA 101 Type II properties including:

- Break Strength
- Tear Strength
- Cold Crack
- Heat Aging
- Shrinkage
- Stain Resistance
- Coating Adhesion (Bond)
- Colorfastness
- Washability
- Scrubability
- Blocking
- Crocking

**Specifications:**

Federal Specification:

CCC-408-D Type II\*

WA Specification:

WA-101 , NSF/ANSI 342 Sustainability Standard

NFPA Life Safety Code 101\*

**Fire Test Ratings:**

- ASTM-E84 Tunnel Test Passed Class A
- EU Class Flame (EN15102) Passed Class B, s2



BS476 Parts 6&7  
CAN/ULC-S102

Passed all requirements  
Passed all requirements

**Mold/Mildew:** ASTM-G21 Specifications Passed all requirements

**Sustainability:** NSF-342 - Certified for Silver compliance for all 20 oz wallcovering constructions  
HPD – Health Product Declaration available  
Low VOC – Meets California CDPH Standard for Schools and Offices when tested to CA 01350  
Contributes to LEED v4  
Meets or exceeds EU Toxicity standard EN 12149 A,B,C for heavy metals and formaldehyde  
Phthalate free formulation  
Prop 65 compliant  
Manufactured without the use of Brominated flame retardants  
For non-woven backed constructions –  
11% post-consumer content in total product – using recycled polyester, cellulose  
100% of backing fiber content is post-consumer fiber

**Warranty:** 5 Year Warranty against manufacturing defects. Additional information regarding warranty is available on our website at <http://www.dreamscapewalls.com/> (<http://www.dreamscapewalls.com/>).

**Comments:** \*Meets or exceeds requirements for flame spread, smoke developed and flashover.

**DreamScape – a division of Roysons Corp. · 40 Vanderhoof Ave. · Rockaway, NJ 07866**

--	--	--

