


WALL + FLOOR WRAPS

PERMANENTLY REMOVABLE

C A V I A R + R A V E L L O

- 3 Ply Durability
- Phthalate-Free
- Clean Vinyl Technology

- Grip Texture
- Slip Resistant Certified
- ANSI A137.1 & Pendulum DCOF



PRINT WITH LATEX, SOLVENT & UV-CURABLE INKS

F L O O R S **W A L L S** **C O U N T E R S**



WALL + FLOOR WRAPS

PERMANENTLY REMOVABLE

CAVIAR + RAVELLO

EFFORTLESS, HIGH IMPACT THEMATIC GRAPHICS

HIGHLY DURABLE 3 PLY MATERIAL

ONE STEP - NO OVERLAMINATION NECESSARY

REPOSITION/APPLY MULTIPLE TIMES

APPLY ACROSS WALLS, OVER MOLDINGS, AROUND CORNERS, ON CEILINGS, COUNTERS, CARPETS & FLOORS

2-4 TIMES THICKER THAN OTHER WRAPS, WILL NOT STRETCH OR TEAR EASILY

UNIQUE TEXTURE HIDES WALL IMPERFECTIONS, REDUCES GLARE & LIGHT HOT SPOTS

GRITTY TEXTURE PROVIDES SLIP RESISTANCE

PERFECT FOR WALL & FLOOR GRAPHICS, TRADE SHOW DISPLAYS, WIDE FORMAT MURALS, POP, CUSTOM PROMOTIONS, SEASONAL OR EVENT THEMING, INTERIOR FLOORS, LOW PILE CARPET, CONCRETE TILE & WOOD

Product Packaging

Each roll is meticulously packaged in a re-usable tube. No splices, no creases, no flat spots for printer efficiency.

STD Lengths: 75' 150' 300' | Width: 54" (+/- 1/8")

Physical Properties

Product Weight: 20.5 oz. per lineal yd with paper lining / 15 oz without lining

Film Weight: 14.5 oz. per lineal yd

Film Thickness: 0.013 in.

Cold Crack Resistance @ 20F - no change

Heat Aging 7 days @ 158F - no change

Adhesive Properties

- Acrylic Based - Fire Retardant - Non Permanent
- Low Tack and Peel - can be repositioned with no adhesive residue on removal

- Adheres to almost any smooth surface

- Tested on dry wall, glass, metal, wood paneling, display board, tile, concrete, low pile carpet and hardwood floor

- Shrinkage - Edge shrinkage of 1mm to 2mm is possible in the first 30 days

For best results follow the DreamScape Wall + Floor Wraps Install Instructions.

Removability

When applied properly on a suitable surface, the adhesive will maintain it's standard release for 2 years. Beyond 2 years, the bond strength with the surface may gradually increase.

Durability and Longevity

Wall: 5-10 Years / Floor: 4-6 months / Counters: 1-2 years

*longevity estimates do not account for ink variables

**product shelf life: 1 year

Application

- Drywall requires a sealed surface with a level 4 or 5 finish.

- Uncured paints and primers can result in poor adhesion.

- Never apply over fresh paint, dusty or dirty surfaces.

- Not for use on granite or marble. Surface must be clean and dry.

Avoid solvent or ammonia based cleaners. Always clean surface with a mild detergent and water and dry thoroughly prior to application.

- Carpet should be low pile, short, tightly woven, and have minimal texture

Exclusions: outdoor, external ramps, commercial kitchens, serving areas behind bars, cold stores and freezers, loading docks under cover, communal shower rooms, swimming pool decks, swimming pool ramps or stairs, wet treads or landings

Due to the variability of surfaces, sealers, paints and environmental conditions, DreamScape does not accept claims for application or removal failures. It is the user's obligation to test and verify suitability prior to application. Purchaser must ensure that the ink applied does not degrade the product's slip resistance; and is responsible for the design and selection of product applications.

Flame Certification

ASTM E84-Class A • ASTM E648 - Class 1 • NFPA Life Safety Code 101

Floor Slip Certifications

- ANSI A137.1/A326.3 AVG DCOF .49

- AS HB198:2014 Pendulum Test Dry 59 Wet 36

Warranty

DreamScape limited & exclusive warranty for Caviar or Ravello Wall + Floor Wraps available upon request

GRIP TEXTURES:

· Texture Hides Wall Imperfections



· Slip Rated for Flooring

